



DRIEAZ LGR 7000XLI DEHUMIDIFIER

Portable, high-performance water removal – even at low humidity levels. Reduce and control excess moisture fast with the unit’s patented cross-flow technology that optimizes moisture removal in virtually all conditions. The i-Series digital control displays real-time temperature, relative humidity and GPP, and offers an adjustable humidistat for precise moisture control.



Features:

- Advanced Crossflow Technology maximizes efficiency and ensures superior performance in low-grain conditions
- Built-in sensors monitor performance parameters; system automatically adjusts operation to optimize performance in all conditions
- Built-in humidistat and plain-English system status and maintenance-related messages
- Sealed large-capacity pump basin – large enough to contain water from an unintentional defrost after a power outage or other unexpected shut-down
- Ergonomic design. Handle 2 in. taller for easier use on stairs, folds down for storage. Integrated cord and hose storage.
- Legendary rotomolded housing – practically indestructible stackable for storage to save space
- Automatic restart after outage when power is restored.

SPECIFICATIONS

WATER REMOVAL AHAM (80°F/60%RH):	130 pts. 61.5 L / day
MAX. WATER REMOVAL (SATURATION):	.235 pts. 111 L / day
PROCESS AIR (MAX.):	325 CFM 552 CMH. Floor-level outlet.
DIMENSIONS (W×H×D):	20 x 33.5 x 20 in. 51 x 85 x 51 cm
USE WEIGHT:	107 lbs. 49 kg
AMPS:	8.3A
VOLTS:	115V
FREQUENCY:	60Hz
POWER CORD:	25 ft. 7.6 m
DRAIN HOSE:	40 ft. 12.2 m
FILTER TYPE:	4-PRO filter
OPERATING RANGE:	33°F-100°F 1°C-38°C
HOUSING:	Rotomolded polyethylene
SAFETY:	ETL listed to CSA 22.2 no. 92
XACTIMATE:	WTRDHM>>XL

