



AXIS
PORTABLE AIR

OCEANAIRE AIR CONDITIONER

OWC1811 – 1.5 TON

DELUXE PORTABLE WATER COOLED SPOT COOLING AIR CONDITIONER


- Cooling Capacity is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- CFM with free discharge
- Amps & Watts at 115 Volts




Features:

COOLING AMBIENT OPERATING RANGE 65° TO 105°. NOT APPROVED FOR OUTDOOR USE


- Solid state electronic controller
- Automatic 6-speed fan control with manual override
- Large LED display
- Swivel ball bearing casters with locks at front
- Internal condensate pump with overflow alert
- LCDI power cord
- High pressure safety switch
- Washable electrostatic air filter




NK-2 (2x6") Nozzle Kit for Directional Cooling/Heating



DDA-10 Discharge Duct Adapter for Extended Single Duct Length



2DEP-12 Evaporator Return Air Plenum



HK-1 3/8"x10' Hose Kit
HK-2 3/8"x25' Hose Kit
HK-3 3/8"x40' Hose Kit



OWC1811 DELUXE PORTABLE WATER COOLED SPOT COOLING AIR CONDITIONER

SPECIFICATIONS

COOLING CAPACITY	18,000 BTUH
VOLTAGE	115 V, 60 Hz, Single Phase
AMPS	11.3 A
WATTS	1300 W
IN RUSH AMPS	69 A
EER	13.8
COMPRESSOR TYPE	Rotary
COMPRESSOR MOTOR	1-1/2 HP
COMPRESSOR RLA	12.3 A
EVAPORATOR BLOWER	Centrifugal
EVAP CFM - HIGH	600
EVAP MOTOR HP	1/8 HP
EVAP MOTOR AMPS	1.8 A
CONDENSER	Coaxial
COND GPM AT EWT, 60°F	1.1 GPM
COND GPM AT EWT, 85°F	4.5 GPM
POWER CORD	14/3
PLUG TYPE	5-15P, LCDI
CORD LENGTH	10 FT
CONDENSATE REMOVAL	Pump-Automatic
LIFT (VERTICAL)	20 FT
REFRIGERANT CHARGE	18 OZ., R-410A
HEIGHT W/ CASTER	39-3/4 in
HEIGHT W/O CASTER	34-1/2 in
WIDTH	24-1/4 in
DEPTH	13 in
NET WEIGHT	155 lb

