



AXIS
PORTABLE AIR

OCEANAIRE AIR CONDITIONER

OWC6012 – 5 TON

DELUXE PORTABLE WATER COOLED SPOT COOLING AIR CONDITIONER


- Cooling Capacity is total BTUH at 80°DB/67°WB return air, 95°F Outdoor at high fan speed
- Dedicated Circuit and Time Delay fuses/circuit breakers are recommended
- CFM with free discharge
- Amps & Watts at 208 Volts




Features:

COOLING AMBIENT OPERATING RANGE 65° TO 105°. NOT APPROVED FOR OUTDOOR USE


- Solid state electronic controller
- Automatic 6-speed fan control with manual override
- Large LED display
- Swivel ball bearing casters with locks at front
- Internal condensate pump with overflow alert
- LCDI power cord
- High pressure safety switch
- Washable electrostatic air filter




2NK-3 (2x8") Nozzle Kit for Directional Cooling/Heating



2DDA-16 Discharge Duct Adapter for Extended Single Duct Length



DEP-16 Evaporator Return Air Plenum



HK-3 5/8"x10' Hose Kit
HK-4 5/8"x25' Hose Kit
HK-6 5/8"x40' Hose Kit



OWC6012 DELUXE PORTABLE WATER COOLED SPOT COOLING AIR CONDITIONER

SPECIFICATIONS

COOLING CAPACITY	60,100 BTUH
VOLTAGE	208-230 V, 60 Hz, Single Phase
AMPS	23.7 A
WATTS	5000 W
IN RUSH AMPS	165 A
EER	12
COMPRESSOR TYPE	Scroll
COMPRESSOR MOTOR	5 HP
COMPRESSOR RLA	27.6 A
COMPRESSOR LRA	158 A
EVAPORATOR BLOWER	Centrifugal
EVAP CFM - HIGH	1950
EVAP MOTOR HP	1 HP
EVAP MOTOR AMPS	5.2 A
CONDENSER	Coaxial
COND GPM AT EWT, 60°F	3.8 GPM
COND GPM AT EWT, 85°F	15.0 GPM
POWER CORD	10/3
PLUG TYPE	6-30P, LCDI
CORD LENGTH	10 FT
CONDENSATE REMOVAL	Pump-Automatic
LIFT (VERTICAL)	20 FT
REFRIGERANT CHARGE	52 OZ., R-410A
HEIGHT W/ CASTER	51-1/2 in
HEIGHT W/O CASTER	45-1/4 in
WIDTH	27 in
DEPTH	29 in
NET WEIGHT	375 lb

