



AXIS
PORTABLE AIR



HEAVY-DUTY ELECTRIC HEATERS

ELECTRIC HEAT CATALOG

AXISAIR.COM | 888.360.2739



AXIS
PORTABLE AIR



1.5kW 120V HEATER

5,100 BTU/HR **E1.5**

BTU/HR	5,100
WATTS	1,500
AMPS	12.5
VOLTAGE	120V 1-Phase
AIRFLOW	116 CFM
CORD	10' (12 awg)
PLUG	NEMA 5-15P
DECIBELS	47 dB(A) 1m



FEATURES:

- Thermostatically controlled
- Overheat protection at 104F
- Durable steel casing with powder coating stays cool while heater is running
- Stainless jacketed heating coils
- For heating, drying, and ventilating




WEIGHT: **14 lbs**

3kW 240V HEATER

10,200 BTU/HR **E3**

BTU/HR	10,200
WATTS	3,000
AMPS	12.5
VOLTAGE	240V 1-Phase
AIRFLOW	205 CFM
CORD	10' (16 awg)
PLUG	NEMA 6-15P
DECIBELS	50 dB(A) 1m



FEATURES:

- Thermostatically controlled
- Overheat protection at 104F
- Durable steel casing with powder coating stays cool while heater is running
- Stainless jacketed heating coils
- For heating, drying, and ventilating
- Works on 208V



WEIGHT: **20 lbs**

6kW 240V HEATER

20,500 BTU/HR **E6**

BTU/HR	20,500
WATTS	6,000
AMPS	25
VOLTAGE	240V 1-Phase
AIRFLOW	250 CFM
CORD	10' (8 awg)
PLUG	NEMA 14-30P
DECIBELS	53 dB(A) 1m



FEATURES:

- Thermostatically controlled
- Overheat protection at 104F
- Durable steel casing with powder coating stays cool while heater is running
- Stainless jacketed heating coils
- For heating, drying, and ventilating
- Works on 208V
- Plugs into a standard dryer outlet



WEIGHT: **33 lbs**





9kW 240V HEATER

30,700 BTU/HR **E9**

BTU/HR	30,700
WATTS	9,000
AMPS	37.5
VOLTAGE	240V 1-Phase
AIRFLOW	350 CFM
CORD	10' (8 awg)
PLUG	NEMA 14-30/50P
DECIBELS	55 dB(A) 1m



FEATURES:

- Thermostatically controlled
- Overheat protection at 104F
- Durable steel casing with powder coating stays cool while heater is running
- Stainless jacketed heating coils
- For heating, drying, and ventilating
- Works on 208V
- Plugs into a standard dryer outlet



WEIGHT: **40 lbs**

18kW 240V HEATER

65,000 BTU/HR

	18E-1	18E-3
BTU/HR	65,000	65,000
WATTS	18,000	18,000
AMPS	81	47
VOLTAGE	240V 1-Phase	240V 3-Phase
AIRFLOW	590 CFM	590 CFM
CORD	Not Included	Not Included
PLUG	Not Included	Not Included
DECIBELS	58 dB(A) 1m	58 dB(A) 1m



FEATURES:

- Thermostatically controlled
- Three Modes: Fan Only, 13kW, & 18kW.
- Overheat protection at 104F
- Durable steel casing with powder coating stays cool while heater is running
- Stainless jacketed heating coils
- For heating, drying, and ventilating
- Works on 208V



WEIGHT: **62 lbs**

480V/575V HEATERS

136,500 - 205,000 BTU/HR

	40E	40ECA	60E
BTU/HR	136,500	136,500	205,000
WATTS	40,000	3,000	60,000
AMPS	60	50	75
VOLTAGE	480V 3-Phase	575V 3-Phase	480V 3-Phase
AIRFLOW	1765 CFM	1765 CFM	1765 CFM
CORD	N/A	N/A	N/A
DUCT DIA.	14"	14"	14"
DECIBELS	82 dB(A) 1m	82 dB(A) 1m	82 dB(A) 1m



FEATURES:

- Thermostatically controlled
- Three Modes: Fan Only, 13kW, & 18kW.
- Overheat protection at 104F
- Durable steel casing with powder coating stays cool while heater is running
- Stainless jacketed heating coils
- For heating, drying, and ventilating
- Works on 208V



WEIGHT: **125 lbs**





PHASE	VOLTAGE	AMPS	MODEL	BTU/HR	PLUGS
SINGLE PHASE	110V 120V	12.5	E1.5	5,100	 NEMA 5-15P
	208V 240V	12.5	E3	10,200	 NEMA 6-15P
		25	E6	20,500	 NEMA 14-30P
		37.5	E9	30,700	 NEMA 14-50P
		81	18E-1	65,000	CABLE/PLUG NOT INCLUDED
		47	18E-3	65,000	
480V	50	40E	136,500		
	75	60E	205,000		
575V	41	40ECA	136,500		
3 PHASE					

AXIS PORTABLE AIR

4132 W. Venus Way
Chandler, AZ 85226

