



## PHOENIX AAM AXIAL AIR MOVER

### 3000+ CFM PATENTED FOCUS™ TECHNOLOGY

The Phoenix Axial Air Mover revolutionized evaporative drying by producing 3000 CFM of airflow while using less than 2.5 amps of electricity (high speed). The Phoenix Axial Air Mover is the industry's only air mover specifically engineered with patented Focus™ Technology.



Focus™ Technology not only produces air velocities greater than competitive products, but also focuses those velocities on hard-to-dry areas such as carpet and pad, sub-floor and walls.

The Phoenix Axial Air Mover operator interface is conveniently located for easy access and features a power indicator lamp, a 3-position switch, an hour meter, a GFCI outlet, and a circuit breaker, eliminating nuisance trips to the breaker box.

## Features:

- Less than 2.5 amps on High Speed
- Power-on indicator light
- Automatic hour meter displays site run time
- On-board power management:
- Circuit breaker protects air mover and attached devices and prevents nuisance visits to the junction box
- GFCI protection promotes operator safety in wet applications
- Duplex AC outlet allows daisy chaining of up to four axial air movers
- 20 ft AC cord with cord management
- Units interlock for ease of stacking during storage and handling
- Weighs 2.5 lbs less than competitive units
- Over 3000 CFM on high



# PHOENIX AAM - AXIAL AIR MOVER

## SPECIFICATIONS

<b>PART NUMBERS</b>	4025200 (Red)		
	4030680 (Blue)		
<b>POWER</b>	Current Draw: 2.5 Amps (High Speed)		
	Voltage: 115 VAC, Grounded		
<b>DRIVE MOTOR</b>	1/4 hp 1-phase 110/120 VAC 2-speed 4-pole, PSC Electric motor		
<b>CFM</b>	Approximately 3000 CFM		
<b>OUTLET</b>	15A UL Rated GFCI Duplex Receptacle		
<b>CORD</b>	20 ft Power Cord		
<b>DIMENSIONS</b>	<b>Units</b>	<b>Shipping</b>	
	WIDTH	19.125"	19.375"
	HEIGHT	19.5"	20"
	DEPTH	15.2"	15.5"
	WEIGHT	29.5 lbs	32.7 lbs
<b>ACCESSORIES &amp; REPLACEMENT FILTERS</b>	4025092 Motor		
	4025095 Blade		
	4021597 Hour Meter		
	4025205 GFCI Duplex Outlet		
	4025203 Circuit Breaker		
	4025460 AAM Stand		
<b>WARRANTY</b>	Year 1 - 100% of Parts and Labor		
	Year 2 100% Parts only (all components)		
	Years 3-7 - Materials and workmanship of the housing only.		
<b>PATENTS</b>	7,331,759		



Innovative control panel includes power-on light, run-time hour meter, GFCI outlet and more.



Units interlock for ease of stacking during storage and handling.

