

PRODUCT SPECS

THE GREENTHAW™ SYSTEM 650 GTS

For ground thaw, concrete curing, building heat, dehumidification, fluid heating and oil and gas applications

GREENTHAW™ BY DRYAIR:

Maximizing your energy with innovative features. Focused on dramatically reducing fuel consumption, making it the most environmentally friendly cost efficient system on the market today!



UNMATCHED TEMPERATURE CONTROL

The DryAir Greenthaw™ system gives you almost perfect control over the temperature of your concrete pour. By adjusting the 'flow reverser controller' to the recommended schedule, every square foot of your concrete pour will receive the same amount of heat. The uniform curing pattern eliminates problems caused by uneven curing.

MORE VERSATILITY

The large 620,000 Btu heater provides you with ample Btu's.

If you wish to utilize this extra Btu capacity, you can A) lay out more ground thaw hose or B) while thawing, also provide structure heat utilizing DryAir's portable heat exchangers.

OUTSTANDING COMBUSTION RELIABILITY

DryAir's patented CEC (combustion environment control) system preheats the combustion air and fuel to provide the burner with an ideal combustion environment in the widest range of ambient conditions.

Wide outside temperature swings will not affect the DryAir's 650 GTS GreenThaw™—it hums right along!

LARGE HOSE REEL CAPACITY

With 5,000 linear ft of hose on board, the 650 GTS offers over 66% more thawing or curing capability than the most common ground thaw units on the market.

ENCLOSED TRAILER OFFERS CONVENIENCE AND EASE

DryAir's enclosed design not only offers ease of operation and convenience, we also continue to honor our tradition of excellent service access to all components.



400 Service Road, St. Brieux, SK, S0K 3V0, Canada
1-888-750-1700 | WWW.DRYAIR.CA

PRODUCT SPECS

THE GREENTHAW™ SYSTEM

650 GTS *cont'd*

GREENTHAW™ FLOW REVERSER

Check out further
details on the
innovative *GreenThaw™*
Flow Reverser by
scanning the video QR
codes below!



EVEN HEAT



THAW PATTERN

SPECIFICATIONS

Trailer dimensions:

195" l x 94" w x 96" h

Weight 10,250 lbs

Burner.....Single stage

Fuel:

Diesel

Input capacity

- 620,200 Btu/h

Consumption (100% run time)

- 4.43 US gph

Diesel fuel capacity:

250 US gal

Thawing capacity (max):

- 7,500 sq ft (std),
11,000 sq ft (w/acc)*

Curing capacity (max):

- 10,000 sq ft (std),
25,000 sq ft (w/acc)*

Heating capacity (area):

- 19,000 sq ft

Heat transfer fluid (HTF) circulation system:

HTF

- non-toxic propylene
glycol/water

Maximum operating temperature

- 180°F

Maximum operating pressure

- 35 psi

Flow

- 1,175 gph

HTF flow reversing system

- adjustable cycle,
temperature optimizing dial

Climate control system:

Diesel fuel heater

- maintains set fuel
temperature

Combustion air heater

- maintains set combustion
air temperature

Controls and monitoring:

Pump and temperature controls, full
gauge panel showing circulation
fluid temperatures and pressures,
fuel pressures, 8-light system
operation feature for easy system
troubleshooting, external operating
light

Powered hose reel (controls):

variable speed forward/reverse or
freewheel, foot switch activation

Circulation loop length (max):

1,000 ft

Circulation loop length (min):

500 ft

Onboard hose (max):

5,000 ft

Manifold 10-port, 3/4" quick
connects

Optional:

- Multiquip 7 kW
- Bolt-on lifting frame
- Light tower

*Additional hose and accessories are needed to
reach the maximum thawing and curing capacities
listed above. For best results, DryAir recommends a
maximum hose spacing of 18" for thawing and 24"
for curing. With that spacing, the 5,000 ft of hose
onboard the 650 GTS would provide a maximum
coverage of 7,500 sq ft for thawing or 10,000 sq ft
for curing.